

Safety Data Sheet
Micro-Dry

SECTION I - IDENTIFICATION

PRODUCT NAME: Micro-Dry
PRODUCT CODE: 5660
PRODUCT USE: Dry Lubricant
COMPANY NAME: QuestVapco Corporation
COMPANY ADDRESS: PO Box 624 Brenham, TX 77834
COMPANY PHONE: 1-800-231-0454
EMERGENCY PHONE: 800-255-3924

SECTION II – HAZARDS IDENTIFICATION

CLASSIFICATION: Flammable Aerosol: Category 1
Liquefied Gas
Skin Irritant: Category 2
Eye Irritant: Category 2A
Specific Target Organ Toxicity (Single Exposure): Category 3
Aspiration Hazard: Category 1

HAZARD STATEMENT(S): DANGER: Extremely Flammable Aerosol Contains gas under pressure: May explode if heated. Causes skin and serious eye irritation. May cause drowsiness and dizziness. May be fatal if swallowed and enters airways.

This product contains the following percentage of chemicals of unknown toxicity: 0%

PRECAUTIONARY STATEMENTS: Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves and eye protection. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Avoid breathing fumes, mist, vapors, and spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Store locked up. Dispose of contents and container in accordance with local, state, and national regulations.



SYMBOL:

HAZARDS NOT OTHERWISE CLASSIFIED: N/A

SECTION III – COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	CAS NUMBER	PERCENT
Heptane	142-82-5	10-30%
Isopropyl Alcohol	67-63-0	7-13%
Propane/n-Butane	68476-86-8	30-60%
Isoparaffinic Hydrocarbon	64741-66-8	15-40%

SECTION IV - FIRST AID MEASURES

EYES: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

INGESTION: If swallowed: Rinse mouth. Do NOT induce vomiting. Get medical advice or attention.

INHALATION: Move to fresh air. If breathing is difficult, administer oxygen. If not breathing administer artificial respiration. Seek medical attention if irritation persists.

SKIN: If on skin: Wash with plenty of water. If skin irritation occurs: get medical attention.

ACUTE HEALTH HAZARDS: Eyes: redness, tearing, blurred vision

Skin: defatting and dermatitis

Inhalation: Anesthetic, irritation, Central Nervous System depression

Oral: abdominal irritation, nausea, vomiting, diarrhea, aspiration risk

Safety Data Sheet

Micro-Dry

CHRONIC HEALTH HAZARDS: Repeated or prolonged exposure may be toxic to kidneys, liver, skin, central nervous system (CNS).

NOTE TO PHYSICIAN: If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

SECTION V – FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA: Dry chemical, foam, or Carbon Dioxide (CO₂).

UNSUITABLE EXTINGUISHING MEDIA: Water spray/stream.

SPECIAL FIRE FIGHTING PROCEDURES: Wear NIOSH approved Self Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires. Use water spray only to cool exposed containers. Shut off all sources of ignition.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Keep away from sparks, open flames, and hot surfaces. No smoking. Do not spray on an open flame or other ignition source. May develop a flammable atmosphere in confined areas.

HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon

SECTION VI – ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTIVE EQUIPMENT: Refer to section VIII for proper Personal Protective Equipment.

SPILL: Clean up with non-combustible material like vermiculite, sand or earth. If many cans are opened remove ignition sources. Prevent spill from entering sewers, storm drains, and natural waterways.

WASTE DISPOSAL: Dispose of in accordance with federal, state, and local regulations.

RCRA STATUS: Waste likely considered D001, under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION VII – HANDLING AND STORAGE

HANDLING AND STORAGE: Protect from sunlight. Store in a well ventilated place. Do not expose to temperatures exceeding 50°C/122°F. Pressurized container: Do not pierce or burn, even after use. Store locked up.

OTHER PRECAUTIONS: Keep out of the reach of children.

INCOMPATIBILITY: Oxidizers, heat, sparks, open flame, and energized equipment.

SECTION VIII – EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS INGREDIENT	OSHA PEL	ACGIH TLV
Heptane	400 ppm	400 ppm
Isopropyl Alcohol	400 ppm	200 ppm
Propane/n-Butane	1000 ppm	1000 ppm
Isoparaffinic Hydrocarbon	400 ppm	400 ppm

ENGINEERING CONTROLS / VENTILATION: Use only outdoors or in a well-ventilated area.

RESPIRATORY PROTECTION: Use only in well ventilated areas. If exposure levels are exceeded then organic vapor cartridge respirator or SCBA will be needed.

PERSONAL PROTECTIVE EQUIPMENT: Safety glasses and chemical resistant gloves

ADDITIONAL MEASURES: Wash hands thoroughly after handling.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: White Hazy Spray

ODOR: Petroleum odor

ODOR THRESHOLD: N/D

BOILING POINT: N/D

FREEZING POINT: N/D

FLAMMABILITY: Extremely Flammable Aerosol

FLASH POINT: N/D

AUTOIGNITION TEMPERATURE: N/D

LOWER FLAMMABILITY LIMIT: N/D

UPPER FLAMMABILITY LIMIT: N/D

VAPOR PRESSURE (mm Hg): 124

Safety Data Sheet
Micro-Dry

VAPOR DENSITY (AIR=1): > 2
EVAPORATION RATE: >2.5
SPECIFIC GRAVITY (H2O=1): 0.725
pH: N/A
SOLIDS (%): N/D
SOLUBILITY IN WATER: Non-soluble
PARTITION COEFFICIENT: n-OCTANOL/WATER (K_{ow}): N/D
VOLATILITY INCLUDING WATER (%): 99 %
VOLATILE ORGANIC COMPOUNDS (VOC): 71%
DIELECTRIC STRENGTH (Volts): N/D
DECOMPOSITION TEMPERATURE: N/D
VISCOSITY: N/D

SECTION X – STABILITY AND REACTIVITY DATA

REACTIVITY: None Known
CHEMICAL STABILITY: Stable
CONDITIONS TO AVOID: Temperatures greater than 122°F and sources of ignition.
INCOMPATIBILITY: Oxidizers, heat, sparks, open flame, and energized equipment.
HAZARDOUS DECOMPOSITION OR BY-PRODUCT: Oxides of carbon
POSSIBLE HAZARDOUS REACTIONS: None Known

SECTION XI – TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: **Heptane** (142-82-5) LD₅₀ (Oral, Rat) 15,000 mg/kg; LC₅₀ (Inhalation, Rat, 4hr) 103 g/m³; LD₅₀ (Dermal, Rabbit) 2,000 mg/kg **Isopropyl Alcohol** (67-63-0) LD₅₀ (Oral,Rat) 5045 mg/kg; LD₅₀ (Oral, Rabbit) 5045 mg/kg; LD₅₀ (Dermal, Rabbit) 12,800 mg/kg; LC₅₀ (Inhalation, Rat, 8hr) 16,000 ppm

ROUTES OF ENTRY: Eyes, Ingestion, Inhalation, Skin
EYES: Causes irritation, redness, tearing, pain, blurred vision.
INGESTION: May be harmful if swallowed. Not an expected route of exposure. Nausea, vomiting, headaches, abdominal pain, diarrhea, dizziness, pulmonary edems, unconsciousness or death
INHALATION: Anesthetic. Irritates respiratory tract. Acute overexposure can cause serious nervous system depression. Vapor harmful.
SKIN: Brief contact is not irritating. May cause irritation, dryness, redness, localized defatting with prolonged or repeated contact. Removes natural oils and fats from skin.
MEDICAL CONDITION AGGRAVATED: Asthma, bronchitis, emphysema and other lung diseases and chronic nose, sinus or throat conditions. Skin irritation may be aggravated in individuals with existing skin disorders.
ACUTE HEALTH HAZARDS: Eyes: redness, tearing, blurred vision
Skin: defatting and dermatitis
Inhalation: Anesthetic, irritation, Central Nervous System depression
Oral: abdominal irritation, nausea, vomiting, diarrhea, aspiration risk
CHRONIC HEALTH HAZARDS: Repeated or prolonged exposure may be toxic to kidneys, liver, skin, central nervous system (CNS).
CARCINOGENICITY: OSHA: No ACGIH: No NTP: No IARC: No OTHER: No

SECTION XII – ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: **Isopropyl Alcohol** (67-63-0) LC₅₀ (Fathead Minnow, 96 hrs) 100,000 mg/L
BIODEGRADABILITY: Component or components of this product are not biodegradable.
BIOACCUMULATION: This product is not expected to bioaccumulate.
SOIL MOBILITY: This product is mobile in soil.
OTHER ECOLOGICAL HAZARDS: None Known

SECTION XIII – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Dispose of in accordance with federal, state, and local regulations.
RCRA STATUS: Waste likely considered D001, under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

Safety Data Sheet
Micro-Dry

SECTION XIV - TRANSPORTATION INFORMATION

PROPER SHIPPING NAME: Aerosols, Ltd. Qty.
HAZARD CLASS/DIVISION: 2.1
UN/NA NUMBER: UN 1950
PACKAGING GROUP: N/A

AIR SHIPMENT

PROPER SHIPPING NAME: Aerosols, Ltd. Qty.
HAZARD CLASS/DIVISION: 2.1
UN/NA NUMBER: UN 1950

SHIPPING BY WATER:

VESSEL (IMO/IMDG)
PROPER SHIPPING NAME: Aerosols, Ltd. Qty.
HAZARD CLASS/DIVISION: 2.1
UN/NA NUMBER: UN 1950
ENVIRONMENTAL HAZARDS WATER: N/A

SECTION XV - REGULATORY INFORMATION

TSCA STATUS: All Chemicals are listed or exempt.
CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): None
SARA 311/312 HAZARD CATEGORIES: Fire Hazard
SARA 313 REPORTABLE INGREDIENTS: None
STATE REGULATIONS: **Heptane** (142-82-5) California Director's List of Hazardous Substances, Connecticut hazardous material survey, Illinois toxic substances disclosure to employee act, New Jersey RTK, Massachusetts RTK, Minnesota RTK, Pennsylvania RTK, Rhode Island RTK
Isopropyl Alcohol (67-63-0) Right-to-Know acts for Rhode Island, Pennsylvania, Florida, Minnesota, Massachusetts, New Jersey, Tennessee Connecticut hazardous material survey. Isopropyl alcohol Illinois toxic substances disclosure to employee act
INTERNATIONAL REGULATIONS: All components are listed or exempted.

NFPA HEALTH:	1	HMIS HEALTH:	1
NFPA FLAMMABILITY:	3	HMIS FLAMMABILITY:	3
NFPA REACTIVITY:	0	HMIS REACTIVITY:	0
NFPA OTHER:	None	HMIS PROTECTION:	B

SECTION XVI - ADDITIONAL INFORMATION

PREPARATION BY: Jonathon Jarvis
DATE PREPARED: 01/06/2014
REVISION DATE: 02/26/2015

N/A = Not Applicable; N/D = Not Determined

DISCLAIMER: To the best of our knowledge, information contained herein is accurate. However there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.